MATERIAL SAFETY DATA SHEET (DEW)

PRODUCT DESCRIPTION

SECTION 1.

SECTION 2.

MATERIAL IDENTIFICATION

Our Grating and frame are functional, attractive and economical solution to exterior and interior drainage problem provides

a dynamic and contemporary appearance to complement today's architectural spaces. **MATERIAL USED**

Stainless Steel - Grade 430

MANUFACTURER'S NAME

SAKSHI INNOVATIONS PRIVATE LIMITED

Gurudwara Somasar Road, P.O. Sahnewal, Village TIBBA, Distt. LUDHIANA-141 120 (INDIA)

COMPOSITION / INFORMATION ON INGREDIENTS

CAS No.

7440-44-0

% Weight

0.072

16.33

Steel production sheet, coil do not pose a significant health hazardous. However when subjected to Welding, Burning, Sawing, Brazing & grinding etc. Potentially

The alleged health hazards associated with exposure to chromium are dependent

compounds have been reported to cause cancer of the lungs and sinuses. Elementary silicon is an inert material which appears to lack the property of

causing fibrosis in lung tissue. However, slight pulmonary lesions have been

If dust gets on skin wash contaminated area with mild soap and water. Remove

If inhalation of dust / fumes occurs, immediately remove victim from the adverse

No special fire or explosion hazard. Promptly isolate the scene by removing all

Fire Fighters should wear appropriate protective equipment and Equipment of

Safety glasses should always be worn when grinding or cutting. Face shields

Skin covering working clothes, wear dust proof overalls if large quantity of

Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process

According to our experience and information the product has no harmful effects

smoking or using the lavatory and at the end of the working period.

If significant amounts of metal are ingested, seek medical attention.

and wash contaminated clothing if rash or irritation persists, seek medical attention.

Chromium 7440-47-3 Iron 7439-89-6

Chemical Composition

Carbon

■ Iron	<i>7</i> 439-89-6	82.21
Manganese	<i>7</i> 439-96-5	0.616
Phosphorus	<i>77</i> 23-14-0	0.033
Silicon	7440-21-3	0.315
Sulphur	7704-34-9	0.0066
■ Nickel	7440-02-0	0.171
Molybdenum	7439-98-7	0.020
Aluminium	<i>7</i> 429-90-5	0.036
Cobalt	7440-48-4	0.031
Copper	7440-50-8	0.082
Niobium	7440-03-1	0.0069
■ Titanium	7440-32-6	0.0039
■ Vanadium	7440-62-2	0.031
■ Tin	7440-31-5	0.0055
Arsenic	7440-38-2	0.0021
Nitrogen	7727-37-9	0.028
RDS IDENTIFICATION		

Inhalation of fumes from Welding or Burning, Dust from Grinding or Cutting. PRIMARY ROUTE OF EXPOSURE

FLAMMABILITY

CHROMIUM

SILICON

SKIN

INHALATION

INGESTION

ROUTE OF EXPOSURE

& appropriate protective equipment for workers. EFFECT OF SHORT TERM (ACUTE) EXPOSURE

Eye, Skin contact or Inhalation

SKIN CONTACT Dust or particles may cause irritation due to abrasion. Not anticipated under normal circumstances. As such this material is not expected **INGESTION** to be acutely toxic via ingestion. EFFECT OF LONG-TERM (CHRONIC) EXPOSURE

MANGANESE Chronic exposure to high concentrations of manganese fumes and dusts may increase the incidence of bronchitis pneumonia and lung damage and may adversely affect the central nervous system with symptoms resembling

Parkinson's disease.

observable as an x-ray change.

very low toxicity. The hexavalent form is very toxic. NICKEL dermatitis (ACD). Fumes are respiratory irritants and may cause respiratory disease, skin contact can also cause an allergic skin rash, nickel and its

reported in Laboratory animals from intratracheal ingestion of silicon dust. Silicon dust has little adverse effect on lungs and does not appear to produce significant organic disease or toxic effects when exposures are kept under the TLV. Silicon may cause chronic respiratory effects.

environment to fresh air and seek medical attention. If breathing has stopped, certified individuals should perform CPR. Keep affected person warm and at rest.

SECTION 5. FIRE FIGHTING MEASURES **EXTINGUISHER MEDIA** In case of fire, use water spray (Fog), foam, dry chemical extinguisher or Co².

HAZARDOUS COMBUSTION Not applicable for solid form alloy. Toxic metal and metallic Oxide. **PRODUCTS** Fumes may be evolved from fires involving finely divided alloy

persons. Vicinity of the incident if there is a fire.

Minimal problems with spills of this product would be expected to occur because of its solid form. Protective Equipment: Gloves and barrier creams may be necessary to prevent skin sensitization and dermatitis. If your process involves grinding or any other action that causes the release of dust or fumes, approved safety

HANDLING PRECAUTIONS Providing good ventilation and/or local exhaust systems are used.

limits are exceeded.

SECTION 6. ACCIDENTAL RELEASE MEASURES

dust is generated. HYGIENE MEASURES Wash all exposed skin and face thoroughly after handling products before eating,

PHYSICAL STATE Solid **MELTING TEMPERATURE** 1425-1510 °C

on health if properly handled.

REACTIONS

SECTION 11. TOXICOLOGICAL INFORMATION

The product is practically insoluble in water. In views of its consistency and insolubility in water, no ecological Problems are to be expected if the product is

ECHOLOGICAL INFORMATION

TRANSPORT INFORMATION **SECTION 14.**

SARA TITLE III HAZARD Product (Dust and Fume) is categorized as an immediate (acute) health hazard and a delayed (chronic) Health hazard is defined by 40 CFR 370. **CATEGORIZATION**

SARA TITLE III SECTION 302 No components are listed as extremely hazardous substances **EXTREMELY HAZARDOUS**

The information provided herein is Compiled by Sakshi to be accurate from sources believed to be reliable, but it is the responsibility of the user investigate and understand other pertinent sources of information to comply with all laws and procedures applicable to the safe handling and use of this product, and to determine the suitability of the product for its intended use. Sakshi makes no warranty, express or implied, concerning the product or the merchantability or fitness thereof for any purpose or concerning the accuracy of any information provided.

SECTION 3. **EMERGENCY OVERVIEW** Welding, brazing, cutting, grinding and machining of this material may liberate potentially hazardous fumes & dust. This dust or fumes may be harmful if inhaled. Molten material may cause thermal burns.

Not Applicable

hazardous fumes or dust may be generated. Needs adequate exhaust ventilation Fumes & dust may be irritating to respiratory system. INHALATION EYE CONTACT Dust or particles may cause mechanical irritation.

Chronic inhalation of high concentrations of metallic fumes and dusts are associated with the following conditions. IRON OXIDE Chronic inhalation of excessive concentrations of iron oxide fumes or dust may results in development of a benign pneumoconiosis, called siderosis, which is

on its oxidation state. The metal form (chromium as it exists in this product) is of Nickel is a common contact allergen & causes some sensitization, allergic contact

SECTION 4. FIRST AIDS MEASURES **EYES** : If dust/fumes get in eyes, immediately flush with large amounts of running water for several minutes and seek Prompt medical attention.

SUITABLE

SPECIAL EXPOSURE HAZARDS

SPECIAL PROTECTIVE

STORAGE REQUIREMENTS

EYE PROTECTION

SKIN PROTECTION

TECHNICAL MEASURES

DENSITY (G/CM3)

HARDNESS (HV5)

SECTION 12.

FINISH

PACKAGING MATERIAL RECOMMENDED

ENVIRONMENTAL EXPOSURE CONTROLS

Fire Fighters self-contained breathing apparatus (SCBA) with afull face-piece operated in positive pressure mode.

glasses or goggles should be worn SECTION 7. **HANDELING & STORAGE**

Store in a dry place.

Use original container.

SECTION 8. **EXPOSURE CONTROLS/ PERSONAL PROTECTIONS** RESPIRATORY PROTECTION NIOSH / MSHA approved dust/mist/fume respirators should be used during welding, burning and grinding operations, if applicable exposure

should be worn when welding or burning.

equipment will be necessary to reduce emissions to acceptable levels. **PHYSICAL & CHEMICAL PROPERTIES** SECTION 9.

REACTIVITY AND STABILITY SECTION 10. STABILITY The product is stable. POSSIBILITY OF HAZARDOUS Under normal conditions of storage and use, hazardous reactions will Not Occur.

7.750

No.4 or B.A

175

properly handled.

SECTION 13. **DISPOSAL CONSIDERATIONS** METHODS OF DISPOSAL Dispose of in accordance with federal, provincial, state Or local regulations.

Steel scrap should be recycled wherever possible

GENERAL INFORMATION

Material is not listed as a hazardous substance for any mode of transportation.

REGULATORY INFORMATION SECTION 15.

SUBSTANCES (EHSS):

OTHER INFORMATION SECTION 16.