

TECHNICAL DATA SHEET

(FIRM GRIP FLOAT WITH EVA FOAM)



PRODUCT DESCRIPTION

This product is used for making grouting an easy job, as used by professional tillers, this soft foam pad follows the tile surface without marking the face. By leaving a perfect finish with fine looking results.

MATERIAL USED

Float - High impact polystyrene.
Foam - EVA (Ethylene Vinyl Acetate) Foam.

SIZE AND DIMENSIONS:

Description	Length (±2mm)	Width (±2mm)	Foam Thickness (±0.2mm)
140x280x7mm	130	270	7mm
120x240x7mm	110	230	7mm
120x500x10mm	110	490	10mm

PHYSICAL PROPERTIES OF FLOAT:

Property	Test Method	Unit	Nominal Value
Hardness	-	Shore D	75
Flexural Strength	ASTM D790	Kg/cm ²	365
Maximum Melt Temperature	-	OC	180-260

EVA FOAM

Item	Test Method	Specs
Cellular structure	-	Closed Cell
Density (kg/m ³)	-	125 - 160 kg/m ³
Shore (A)Hardness	ASTM-D 2240	15 - 20
Water Absorption by Weight %	-	Low
Temperature	-	Good at low temperature

STORAGE RECOMEDATION

Product should be stored in dry/closed condition at temperature below 50°C and protected from UV/Direct sunlight. Boxes should be open while going to be used.

NOTE

- Product is in compliance with substance of Very High Concern (SVHC) i.e. ≤ 0.1 %w/w as per the candidate list promulgated by the European Chemicals Agency (ECHA) which are defined in Article 57 of REACH Regulation (EC1907/2006) checked by Tuv-Nord Group.