

TECHNICAL DATA SHEET (HYDRO SPONGE)



PRODUCT DESCRIPTION

PU Hydro sponge with very high absorbency. The sponge has open cells which prevent dirt and residues from sticking on it. It Minimizes grout removal from joints. High absorbing foam - for finishing and cleaning surfaces. Suitable for tiling, painting, wallpapering and cleaning.

DIMENSIONAL SPECIFICATION : -

Property	Length (±1.5mm)	Width (±1.5mm)	Height (±1.5mm)
160X110X65 mm	160	110	65
165X110X65 mm	165	110	65
170X115X70 mm	170	115	70
180X110X65 mm	180	110	65

PHYSICAL AND CHEMICAL PROPERTIES: -

Property	Test Method	Unit	Nominal Value
Appearance	-	-	Cellular
Density	-	kg/m ³	27.0
Soluble in water	-	-	insoluble
Decomposition	-	-	> 180 °C
Stability	-	-	-40 °C and 100

STORAGE RECOMEDATION

The Hydro sponge should be stored in dry/closed condition at temperature below 50°C and protected from UV/Direct sunlight.

NOTE

- Product is in compliance with substance of Very High Concern (SVHC) i.e. ≤ 0.1 %w/w as per the candidate list promulgated by the European Chemicals Agency (ECHA) which are defined in Article 57 of REACH Regulation (EC1907/2006) checked by Tuv-Nord Group.