


MATERIAL SAFETY DATA SHEET

(SELF-ADHESIVE BUTYL SEALING SHEET)



SECTION 1. MATERIAL IDENTIFICATION

PRODUCT DESCRIPTION

Self-Adhesive Butyl Sealing Sheet

MATERIAL USED

Butyl Rubber and Poly Propylene Spun Bonded Non Woven Fabric

MANUFACTURER'S NAME

SAKSHI INNOVATIONS PRIVATE LIMITED
Gurudwara Somasar Road, P.O. Sahnewal, Village TIBBA, Distt. LUDHIANA-141 120 (INDIA)

SECTION 2. HAZARDS IDENTIFICATION

Mixture is not hazardous Material.

PBT- This substance is not identified as a PBT substance

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

INGREDIENTS	: PERCENTAGE(%)	CAS No.
BUTYL POLYMER	: 45.86	9010-85-9
POLYISOBUTYLENE	: 28.66	9003-29-6
ZINC OXIDE	: 2.30	1314-13-2
MICRON (CALCITE) POWDER	: 22.93	1317-65-3
CARBON BLACK	: 0.02	1333-86-4
TITANIUM DIOXIDE	: 0.23	2783-94-0

SECTION 4. FIRST AID MEASURES

SKIN CONTACT : Wash immediately with plenty of water and soap

EYE CONTACT : Wash the eye with water for 15 minutes.

INGESTION : Wash out mouth with water

INHALATION : Consult a doctor

SECTION 5. FIRE FIGHTING MEASURES

EXTINGUISH MEDIA : Carbon dioxide or dry chemical extinguishers may be used for small fires.

FIRE FIGHTING PROTECTIVE EQUIPMENT : Wear positive pressure self contained breathing apparatus (SCBA) and protective fire clothing. If protective equipments are not available, fight fire from a protected location or safe distance

SPECIFIC HAZARDS : Burning may release CO, Co2 & H2O vapors.

SECTION 6. ACCIDENTAL RELEASE MEASURES

PERSONAL PROTECTION : Caution: Spillage may be slippery. Ensure suitable personal (Including respiratory protection) during removal of spillages. Dust clouds are sensitive to ignition by electrostatic discharge.

ENVIRONMENT EXPOSURE CONTROL : Avoid release to the environment. Do not allow to enter drains, sewers or watercourses.

METHOD OF CLEANING UP : Sweep up and shovel into waste drums or plastic bags

SECTION 7. HANDLING & STORAGE

HANDLING : Controls dust formation. Do not eat, drink or smoke at the work place. Wash face and hands before eating, drinking or smoking

STORE : Store in cool well-ventilated area. Store in original containers between +5° to 25°C. Store all product indoor and be protected from direct sunlight, extreme heat, cold, frost, moisture, and NOx fumes

SECTION 8. EXPOSURE CONTROLS/ PERSONAL PROTECTIONS

Provide adequate ventilation when the material are processed and follow the principles of good occupational hygiene to control personal exposures.

SECTION 9. PHYSICAL & CHEMICAL PROPERTIES

SPECIFIC GRAVITY : 1.0 - 1.2

PHYSICAL STATE : Pasty solid

COLOR : Grey

VISCOSITY : Highly viscous

ODOR : Characteristics Odor

EVAPORATION RATE : Moderate

SOLUBILITY IN WATER : Not Soluble

SECTION 10. REACTIVITY AND STABILITY

CHEMICAL STABILITY : Stable under normal conditions

CONDITIONS TO AVOID : Heat and direct sunlight

MATERIALS TO AVOID : Direct contact with open flames.

HAZARD DECOMPOSITION PRODUCTS : Carbon monoxide, carbon dioxide, hydrocarbon and Acrid smoke.

SECTION 11. TOXICOLOGICAL INFORMATION

REGULATORY INFORMATION : Do not allow enter drains, sewers or water courses.

SECTION 12. ECHOLOGICAL INFORMATION

Insoluble in water floats on water. The product has low mobility in soil

SECTION 13. REGULATORY INFORMATION

Not classified as dangerous for supply/use

SECTION 14. TRANSPORT INFORMATION

Not classified as dangerous for transport.

SECTION 15. DISPOSAL CONSIDERATION

1. To be recycled wherever possible.
2. Dispose of in accordance with federal, provincial, state or local regulations.

SECTION 16. OTHER INFORMATION

The information stated above is based on our knowledge & available literature / test report. Its purpose is to describe the product from its safety point of view and do not constitute any warranty of characteristics as use of the product are not within our control, it is user's obligation to determine the condition of safe use of the product. Sakshi shall not be held liable for any damage resulting during handling or from contact with the above product