
MATERIAL SAFETY DATA SHEET (EVO VENTILATION WINDOW)



PRODUCT DESCRIPTION

MATERIAL IDENTIFICATION

SECTION 1.

Best suitable for ventilation in bathroom without Corrosion/Rust in Acidic environment.

MATERIAL USED

Stainless Steel - Grade 430

NITEACTUDED'S

MANUFACTURER'S NAME

Gurudwara Somasar Road, P.O. Sahnewal, Village TIBBA, Distt. LUDHIANA-141 120 (INDIA)

SAKSHI INNOVATIONS PRIVATE LIMITED

SECTION 2. COMPOSITION / INFORMATION ON INGREDIENTS

CAS No.

% Weight

0.072

16.33

Welding, brazing, cutting, grinding and machining of this material may liberate

Not anticipated under normal circumstances. As such this material is not expected

Chronic inhalation of excessive concentrations of iron oxide fumes or dust may

increase the incidence of bronchitis pneumonia and lung damage and may adversely affect the central nervous system with symptoms resembling

Nickel is a common contact allergen & causes some sensitization, allergic contact

causing fibrosis in lung tissue. However, slight pulmonary lesions have been reported in Laboratory animals from intratracheal ingestion of silicon dust. Silicon dust has little adverse effect on lungs and does not appear to produce significant organic disease or toxic effects when exposures are kept under the

If dust gets on skin wash contaminated area with mild soap and water. Remove and wash contaminated clothing if rash or irritation persists, seek medical attention.

In case of fire, use water spray (Fog), foam, dry chemical extinguisher or Co².

Fire Fighters self-contained breathing apparatus (SCBA) with afull face-piece

Not applicable for solid form alloy. Toxic metal and metallic Oxide.

Providing good ventilation and/or local exhaust systems are used.

Safety glasses should always be worn when grinding or cutting. Face shields

Skin covering working clothes, wear dust proof overalls if large quantity of

Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process

equipment will be necessary to reduce emissions to acceptable levels.

Wash all exposed skin and face thoroughly after handling products before eating,

■ Carbon 7440-44-0 ■ Chromium 7440-47-3

Chemical Composition

■ Iron	<i>7</i> 439-89-6	82.21
Manganese	7439-96-5	0.616
Phosphorus	<i>77</i> 23-14-0	0.033
Silicon	7440-21-3	0.315
Sulphur	7704-34-9	0.0066
■ Nickel	7440-02-0	0.171
Molybdenum	<i>7</i> 439-98- <i>7</i>	0.020
Aluminium	<i>7</i> 429-90-5	0.036
Cobalt	7440-48-4	0.031
Copper	<i>7</i> 440-50-8	0.082
■ Niobium	7440-03-1	0.0069
■ Titanium	7440-32-6	0.0039
■ Vanadium	7440-62-2	0.031
■ Tin	<i>7</i> 440-31-5	0.0055
Arsenic	7440-38-2	0.0021
■ Nitrogen	7727-37-9	0.028
Note: Also available with White or Black Powder Coating. Coating Thickness (Microns) - 75 - 85		

potentially hazardous fumes & dust. This dust or fumes may be harmful if inhaled.

Molten material may cause thermal burns.

PRIMARY ROUTE OF EXPOSURE : Inhalation of fumes from Welding or Burning, Dust from Grinding or Cutting.

EFFECT OF SHORT TERM (ACUTE) EXPOSURE

HAZARDS IDENTIFICATION

SECTION 3.

FLAMMABILITY

INGESTION

IRON OXIDE

NICKEL

SKIN

SECTION 5.

SECTION 7.

EYE PROTECTION

SKIN PROTECTION

HYGIENE MEASURES

TECHNICAL MEASURES

SECTION 9.

DENSITY (G/CM3)

HARDNESS (HV5)

SECTION 10.

SECTION 12.

METHODS OF DISPOSAL

SECTION 14.

SARA TITLE III HAZARD

EXTREMELY HAZARDOUS SUBSTANCES (EHSS):

FINISH

STABILITY

HANDLING PRECAUTIONS

SUITABLE

EXTINGUISHER MEDIA

HAZARDOUS COMBUSTION

EMERGENCY OVERVIEW

ROUTE OF EXPOSURE

Steel production sheet, coil do not pose a significant health hazardous. However when subjected to Welding, Burning, Sawing, Brazing & grinding etc. Potentially hazardous fumes or dust may be generated. Needs adequate exhaust ventilation

& appropriate protective equipment for workers.

Eye, Skin contact or Inhalation

INHALATION: Fumes & dust may be irritating to respiratory system.EYE CONTACT: Dust or particles may cause mechanical irritation.SKIN CONTACT: Dust or particles may cause irritation due to abrasion.

Not Applicable

EFFECT OF LONG-TERM (CHRONIC) EXPOSURE
: Chronic inhalation of high concentrations of metallic fumes and dusts are

associated with the following conditions.

to be acutely toxic via ingestion.

results in development of a benign pneumoconiosis, called siderosis, which is observable as an x-ray change.

MANGANESE

chronic exposure to high concentrations of manganese fumes and dusts may

Parkinson's disease.

CHROMIUM: The alleged health hazards associated with exposure to chromium are dependent on its oxidation state. The metal form (chromium as it exists in this product) is of

dermatitis (ACD). Fumes are respiratory irritants and may cause respiratory
disease, skin contact can also cause an allergic skin rash, nickel and its
compounds have been reported to cause cancer of the lungs and sinuses.

SILICON: Elementary silicon is an inert material which appears to lack the property of

very low toxicity. The hexavalent form is very toxic.

TLV. Silicon may cause chronic respiratory effects.

SECTION 4. FIRST AIDS MEASURES

EYES

: If dust/fumes get in eyes, immediately flush with large amounts of running water

for several minutes and seek Prompt medical attention.

INHALATION : If inhalation of dust / fumes occurs, immediately remove victim from the adverse environment to fresh air and seek medical attention. If breathing has stopped, certified individuals should perform CPR. Keep affected person warm and at rest.

FIRE FIGHTING MEASURES

INGESTION : If significant amounts of metal are ingested, seek medical attention.

SPECIAL EXPOSURE HAZARDS : No special fire or explosion hazard. Promptly isolate the scene by removing all persons. Vicinity of the incident if there is a fire.

operated in positive pressure mode.

If your process involves grinding or any other action that causes the release of dust or fumes, approved safety glasses or goggles should be worn

PRODUCTS : Fumes may be evolved from fires involving finely divided alloy

SPECIAL PROTECTIVE : Fire Fighters should wear appropriate protective equipment and Equipment of

Minimal problems with spills of this product would be expected to occur because of its solid form.

Protective Equipment: Gloves and barrier creams may be necessary to prevent skin sensitization and dermatitis.

STORAGE REQUIREMENTS : Store in a dry place.

PACKAGING MATERIAL RECOMMENDED :

HANDELING & STORAGE

SECTION 6. ACCIDENTAL RELEASE MEASURES

SECTION 8. EXPOSURE CONTROLS/ PERSONAL PROTECTIONS

RESPIRATORY PROTECTION : NIOSH / MSHA approved dust/mist/fume respirators should be used during welding, burning and grinding operations, if applicable exposure

should be worn when welding or burning.

Use original container.

limits are exceeded.

dust is generated.

smoking or using the lavatory and at the end of the working period. ENVIRONMENTAL EXPOSURE CONTROLS

PHYSICAL & CHEMICAL PROPERTIES

REACTIVITY AND STABILITY

ECHOLOGICAL INFORMATION

TRANSPORT INFORMATION

PHYSICAL STATE : Solid
MELTING TEMPERATURE : 1425-1510 °C

POSSIBILITY OF HAZARDOUS : Under normal conditions of storage and use, hazardous reactions will Not Occur.

REACTIONS

7.750

No.4 or B.A

175

According to our experience and information the product has no harmful effects on health if properly handled.

The product is stable.

properly handled. SECTION 13. DISPOSAL CONSIDERATIONS

SECTION 11. TOXICOLOGICAL INFORMATION

GENERAL INFORMATION : Dispose of in accordance with federal, provincial, state Or local regulations.

Steel scrap should be recycled wherever possible

Material is not listed as a hazardous substance for any mode of transportation. SECTION 15. REGULATORY INFORMATION

: Product (Dust and Fume) is categorized as an immediate (acute) health hazard

The product is practically insoluble in water. In views of its consistency and insolubility in water, no ecological Problems are to be expected if the product is

CATEGORIZATION and a delayed (chronic) Health hazard is defined by 40 CFR 370. SARA TITLE III SECTION 302 : No components are listed as extremely hazardous substances

SECTION 16. OTHER INFORMATION

The information provided herein is Compiled by Sakshi to be accurate from sources believed to be reliable, but it is the responsibility of the user investigate and understand other pertinent sources of information to comply with all laws and procedures applicable to the safe handling and use of this product, and to determine the suitability of the product for its intended use. Sakshi makes no warranty, express or implied, concerning the product or the merchantability or fitness thereof for any purpose or concerning the accuracy of any information provided.