MATERIAL SAFETY DATA SHEET (MATRIX VENTILATION WINDOW)



PRODUCT DESCRIPTION

MATERIAL IDENTIFICATION

SECTION 1.

SECTION 2.

SECTION 3

FLAMMABILITY

INGESTION

IRON OXIDE

CHROMIUM

SKIN

SECTION 5.

SUITABLE

PRODUCTS

SECTION 8.

EYE PROTECTION

HYGIENE MEASURES

TECHNICAL MEASURES

PHYSICAL STATE

DENSITY (G/CM3)

HARDNESS (HV5)

SECTION 10.

SECTION 13.

SECTION 15.

SECTION 16.

GENERAL INFORMATION

STABILITY

MELTING TEMPERATURE

POSSIBILITY OF HAZARDOUS

ENVIRONMENTAL EXPOSURE CONTROLS

EXTINGUISHER MEDIA

HAZARDOUS COMBUSTION

EMERGENCY OVERVIEW

ROUTE OF EXPOSURE

Best suitable for ventilation in bathroom without Corrosion/Rust in Acidic environment.

MATERIAL USED

MANUFACTURER'S NAME

Stainless Steel - Grade 430

SAKSHI INNOVATIONS PRIVATE LIMITED

Gurudwara Somasar Road, P.O. Sahnewal, Village TIBBA, Distt. LUDHIANA-141 120 (INDIA) COMPOSITION / INFORMATION ON INGREDIENTS

Chemical Composition CAS No. % Weight

7440-44-0

0.072

16.33

Welding, brazing, cutting, grinding and machining of this material may liberate

Steel production sheet, coil do not pose a significant health hazardous. However

Not anticipated under normal circumstances. As such this material is not expected

Chronic inhalation of excessive concentrations of iron oxide fumes or dust may results in development of a benign pneumoconiosis, called siderosis, which is

dermatitis (ACD). Fumes are respiratory irritants and may cause respiratory

causing fibrosis in lung tissue. However, slight pulmonary lesions have been reported in Laboratory animals from intratracheal ingestion of silicon dust. Silicon dust has little adverse effect on lungs and does not appear to produce significant organic disease or toxic effects when exposures are kept under the

If dust gets on skin wash contaminated area with mild soap and water. Remove and wash contaminated clothing if rash or irritation persists, seek medical attention.

In case of fire, use water spray (Fog), foam, dry chemical extinguisher or Co².

Safety glasses should always be worn when grinding or cutting. Face shields

Wash all exposed skin and face thoroughly after handling products before eating,

Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process

Under normal conditions of storage and use, hazardous reactions will Not Occur.

According to our experience and information the product has no harmful effects

Dispose of in accordance with federal, provincial, state Or local regulations.

equipment will be necessary to reduce emissions to acceptable levels.

smoking or using the lavatory and at the end of the working period.

Not applicable for solid form alloy. Toxic metal and metallic Oxide.

Fumes may be evolved from fires involving finely divided alloy

Chromium 7440-47-3

Carbon

■ Iron	<i>7</i> 439-89-6	82.21
Manganese	7439-96-5	0.616
Phosphorus	<i>77</i> 23-14-0	0.033
Silicon	7440-21-3	0.315
Sulphur	7704-34-9	0.0066
■ Nickel	7440-02-0	0.171
Molybdenum	<i>7</i> 439-98- <i>7</i>	0.020
Aluminium	<i>7</i> 429-90-5	0.036
Cobalt	7440-48-4	0.031
Copper	<i>7</i> 440-50-8	0.082
■ Niobium	7440-03-1	0.0069
■ Titanium	7440-32-6	0.0039
■ Vanadium	7440-62-2	0.031
■ Tin	<i>7</i> 440-31-5	0.0055
Arsenic	7440-38-2	0.0021
■ Nitrogen	7727-37-9	0.028
Note: Also available with White or Black Powder Coating. Coating Thickness (Microns) - 75 - 85		

potentially hazardous fumes & dust. This dust or fumes may be harmful if inhaled. Molten material may cause thermal burns.

Eye, Skin contact or Inhalation

PRIMARY ROUTE OF EXPOSURE Inhalation of fumes from Welding or Burning, Dust from Grinding or Cutting.

EFFECT OF SHORT TERM (ACUTE) EXPOSURE

HAZARDS IDENTIFICATION

when subjected to Welding, Burning, Sawing, Brazing & grinding etc. Potentially hazardous fumes or dust may be generated. Needs adequate exhaust ventilation & appropriate protective equipment for workers.

INHALATION Fumes & dust may be irritating to respiratory system. EYE CONTACT Dust or particles may cause mechanical irritation. SKIN CONTACT Dust or particles may cause irritation due to abrasion.

Not Applicable

to be acutely toxic via ingestion. EFFECT OF LONG-TERM (CHRONIC) EXPOSURE Chronic inhalation of high concentrations of metallic fumes and dusts are associated with the following conditions.

MANGANESE Chronic exposure to high concentrations of manganese fumes and dusts may

increase the incidence of bronchitis pneumonia and lung damage and may adversely affect the central nervous system with symptoms resembling Parkinson's disease.

observable as an x-ray change.

The alleged health hazards associated with exposure to chromium are dependent on its oxidation state. The metal form (chromium as it exists in this product) is of very low toxicity. The hexavalent form is very toxic. NICKEL Nickel is a common contact allergen & causes some sensitization, allergic contact

disease, skin contact can also cause an allergic skin rash, nickel and its compounds have been reported to cause cancer of the lungs and sinuses. SILICON Elementary silicon is an inert material which appears to lack the property of

TLV. Silicon may cause chronic respiratory effects. FIRST AIDS MEASURES **SECTION 4. EYES** : If dust/fumes get in eyes, immediately flush with large amounts of running water for several minutes and seek Prompt medical attention.

If inhalation of dust / fumes occurs, immediately remove victim from the adverse INHALATION environment to fresh air and seek medical attention. If breathing has stopped, certified individuals should perform CPR. Keep affected person warm and at rest.

FIRE FIGHTING MEASURES

If significant amounts of metal are ingested, seek medical attention. **INGESTION**

SPECIAL EXPOSURE HAZARDS No special fire or explosion hazard. Promptly isolate the scene by removing all persons. Vicinity of the incident if there is a fire.

SPECIAL PROTECTIVE : Fire Fighters should wear appropriate protective equipment and Equipment of Fire Fighters self-contained breathing apparatus (SCBA) with afull face-piece operated in positive pressure mode.

glasses or goggles should be worn SECTION 7. **HANDELING & STORAGE**

Minimal problems with spills of this product would be expected to occur because of its solid form. Protective Equipment: Gloves and barrier creams may be necessary to prevent skin sensitization and dermatitis. If your process involves grinding or any other action that causes the release of dust or fumes, approved safety

SECTION 6. ACCIDENTAL RELEASE MEASURES

Providing good ventilation and/or local exhaust systems are used. HANDLING PRECAUTIONS STORAGE REQUIREMENTS Store in a dry place.

Use original container.

EXPOSURE CONTROLS/ PERSONAL PROTECTIONS

RESPIRATORY PROTECTION NIOSH / MSHA approved dust/mist/fume respirators should be used during welding, burning and grinding operations, if applicable exposure limits are exceeded.

PACKAGING MATERIAL RECOMMENDED :

SKIN PROTECTION Skin covering working clothes, wear dust proof overalls if large quantity of dust is generated.

should be worn when welding or burning.

PHYSICAL & CHEMICAL PROPERTIES SECTION 9.

FINISH No.4 or B.A

REACTIVITY AND STABILITY

175

Solid

7.750

1425-1510 °C

The product is stable.

REACTIONS SECTION 11. TOXICOLOGICAL INFORMATION

SECTION 12. **ECHOLOGICAL INFORMATION** The product is practically insoluble in water. In views of its consistency and insolubility in water, no ecological Problems are to be expected if the product is

DISPOSAL CONSIDERATIONS

METHODS OF DISPOSAL Steel scrap should be recycled wherever possible

properly handled.

on health if properly handled.

TRANSPORT INFORMATION SECTION 14. Material is not listed as a hazardous substance for any mode of transportation.

REGULATORY INFORMATION

SARA TITLE III HAZARD Product (Dust and Fume) is categorized as an immediate (acute) health hazard CATEGORIZATION and a delayed (chronic) Health hazard is defined by 40 CFR 370.

SARA TITLE III SECTION 302

OTHER INFORMATION

No components are listed as extremely hazardous substances **EXTREMELY HAZARDOUS** SUBSTANCES (EHSS):

The information provided herein is Compiled by Sakshi to be accurate from sources believed to be reliable, but it is the responsibility of the user investigate and understand other pertinent sources of information to comply with all laws and procedures applicable to the safe handling and use of this product, and to determine the suitability of the product for its intended use. Sakshi makes no warranty, express or implied, concerning the product or the merchantability or fitness thereof for any purpose or concerning the accuracy of any information provided.