

MATERIAL SAFETY DATA SHEET

(CAULKING SPATULA)



Section 1. MATERIAL IDENTIFICATION

Product name : PROFI FLEX FLOAT
Manufacturer's Name : Sakshi Innovations Private Limited
Address : Gurudwara Somasar Road, P.O. Sahnewal, Village TIBBA, Distt. LUDHIANA-141 120 (INDIA), Ph. 0161-2845136 , email : qa_qc@sakshigroup.org

Section 2. COMPOSITION / INFORMATION ON INGREDIENTS

Natural rubber
Sisamar rubber
Fillers
Lubricants
Curatives
Activators
The product contains no hazardous ingredients

Section 3. HAZARD(S) IDENTIFICATION

Classification of the Substance or Mixture : Not classified as a hazardous material by the OSHA Hazard Communication Standard 29 CFR 1910.1200.

GHS Label Elements:

Hazard symbol :None
Signal word :None

Hazard Statements:No known significant effect or critical hazards.

Precautionary Statements:

Prevention : Not applicable.
Response : Not applicable
Storage : Not applicable.
Disposal : Not applicable.

Hazard(s) not otherwise classified(HNOC) : None known

Section 4. FIRST AID MEASURES

Eye contact : Flush eyes with running water for several minutes while holding eyelids open. If irritation develops, seek medical advice.
Inhalation : Remove to fresh air. Seek medical advice if other symptoms develop.
Skin contact : Wash affected area with soap and water. If irritation develops or persists, seek medical advice.
Ingestion : Seek medical advice if large quantity has been ingested or if you feel unwell.

Most important symptoms/effects, acute and delayed: Potential acute health effects:

Eye contact : Direct contact with eyes may cause temporary irritation.

Inhalation : No known significant effects or critical hazards.

Skin contact : May cause an allergic skin reaction.

Ingestion : Expected to be a low ingestion hazard. Avoid ingestion.

Over-exposure signs/symptoms:

Eye contact : No specific data

Inhalation : No specific data **Skin contact:** No specific data

Ingestion : No specific data

Indication of immediate medical attention and special treatment needed : Treat symptomatically.

Section 5. FIRE FIGHTING MEASURES

Suitable extinguishing method : In case of fire, use water spray (fog), ABC dry chemical.

Unsuitable extinguishing method : Do NOT use water jet.

Specific hazards arising from chemical : During a fire, gases hazardous to health may be formed.

Special protective equipment and precautions for firefighters: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Firefighting equipment/instructions : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Use water spray to cool unopened containers.

Section 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Put on appropriate personal protective equipment.

Methods and materials for containment and cleaning up: Sweep, shovel or scoop up material and place in appropriate container for proper disposal.

Environmental precautions : Do not allow to enter drains, sewers or water courses.

Section 7. HANDLING AND STORAGE

Precautions for safe handling : Do not breathe (dust/vapor/fumes). Wear appropriate personal protective equipment. Wash thoroughly after handling. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities : Store in a cool, dry place away from direct sunlight and incompatible materials.

Section 8. EXPOSURE CONTROL/PERSONAL PROTECTION

Occupational Exposure Limits:None established.

Appropriate engineering controls : Adequate ventilation should be provided so not to exceed exposure limits.

Individual protection measures, such as personal protective equipment:

Eye/face protection : Safety eyewear complying with an approved standard should be used when a risk assessment indicates that there is a risk of exposure to dust/fume at levels exceeding the exposure limit. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.

Skin protection :Hand protection:Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.

Body protection : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Other protection :Appropriate footwear and any additional skin protection measures should be worn to prevent repeated or prolonged skin contact and should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Respiratory protection : Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if there is a risk of exposure to dust/fume at levels exceeding the exposure limit. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.

General hygiene considerations : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

9. Physical & Chemical Properties :

Item	Specs
Shore Hardness D (Durometer)	30 - 35
Water Absorption by Weight %	Very Low
Specific gravity or density	0.91
Solubility in water	Negligible

10. Reactivity & Stability

Stability : Stable material at room temperature.

Condition to avoid : Avoid high temperature.

11. Toxicological Information :

Route of Exposure : Inhalation of vapors melted product and direct contact with skin and eyes, ingestion is not probable.

Acute and chronic effect : Exposure to melted product causes burns. Vapors from melted product may cause irritation to the respiratory tract and eyes. Medical conditions which increase tolerance to exposure: Respiratory, odour and dermatological problems.

12. Ecological Information :

No specific ecological data are available for this product.

13. Disposal Consideration :

Refer to all federal, state, and local regulations before disposition

14. Transport Information :

Refer to all federal, state, and local regulations before disposition

15. Regulatory Information :

Pictograms : NP

Hazard Statements : NP

Precautionary Statements : NP

16. Other Information :

All information contained herein is based on the present state of our knowledge on the date of issue. It is safety to be accurate. It is intended to describe products from the point of view of safety requirements. It should not be construed as guaranteeing specific properties.

Under no circumstances is the user exempt from respecting legislative or administrative requirements related to the product in terms of safety, hygiene, and/or health and environmental protection.

This MSDS was prepared and is to be used only for this product. If the product is used as a component in another product, this MSDS information may not be applicable.

REACH DECLARATION :-Product is in compliance with substance of Very High Concern (SVHC) i.e. $\leq 0.1\%$ w/w as per the candidate list promulgated by the European Chemicals Agency (ECHA) which are defined in Article 57 of REACH Regulation (EC1907/2006) checked byTuv-Nord Group.