
TECHNICAL DATA SHEET

(MOUNT-U)



PRODUCT DESCRIPTION

Mount- U made of 0.70mm galvanized plain steel sheet used as Connectors, to join together solid support and hard foam boards (tile backer boards). It is a simple fast & economical installation. Adjustable mount can revolve at any angle according to requirement. It is suitable to work at narrow places.

MATERIAL USED

Galvanized sheet.

DIMENSIONAL SPECIFICATIONS

Mount-U - 20mm,30mm,40mm,50mm,60mm,80mm NOTE : Tolerance -: ± 0.05mm Coating thickness-: 15 - 20 Micron

PHYSICAL PROPERTIES

■ Density g/cm3 : 7.7■ Hardness (HV5) : 180

CHEMICAL COMPOSITION

Chemical Composition	CAS No.	% Weigh
Carbon	<i>7</i> 440-44-0	0.030
Chromium	7440-47-3	0.0082
lron	<i>7</i> 439-89-6	99.5 <i>7</i>
Manganese	<i>7</i> 439-96-5	0.244
Phosphorus	<i>77</i> 23-14-0	0.015
Silicon	<i>7</i> 440-21-3	0.022
Sulphur	7704-34-9	0.0034
Nickel	<i>7</i> 440-02-0	0.0071
Molybdenum	<i>7</i> 439-98 <i>-7</i>	0.0029
Aluminium	<i>7</i> 429-90-5	0.040
Cobalt	<i>7</i> 440-48-4	0.0031
Copper	<i>7</i> 440-50-8	0.0063
Niobium	<i>7</i> 440-03-1	0.0071
Titanium	<i>7</i> 440-32-6	0.0011
Vanadium	<i>7</i> 440-62-2	0.0008
Tungsten	<i>7</i> 440-33-7	0.0071
Tin	<i>7</i> 440-31-5	0.0018
Nitrogen	7727-37-9	0.0073
' Arsenic	<i>7</i> 440-38-2	0.0016
Boron	<i>7</i> 440-42-8	0.0003
. Cerium	<i>7</i> 440-45-1	0.023
Lead	7439-92-1	0.0030
Magnesium	<i>7</i> 439-95-4	0.0003
Calcium	<i>7</i> 440-70-2	0.0012

STORAGE RECOMEDATION

Product should be stored in dry warehouse with minimum moisture level. For prolonged storage ensure Hammer fix plug are kept elevated above the ground level using timber support. Open the packing only while going to use.

NOTE

Products is in compliance with substance of Very High Concern (SVHC) i.e. ≤ 0.1 %w/w as per the candidate list promulgated by the European Chemicals Agency (ECHA) which are defined in Article 57 of REACH Regulation (EC1907/2006) checked by Tuv-Nord Group.